

1 Elevation
StileLite-200 Series Interior
SCALE : 3/8" = 1'-0"
144



SEE STILES CATALOG FOR OTHER DOOR SELECTIONS

1 Elevation - Door
StileLite-200 Series Interior
SCALE : 3/8" = 1'-0"
144



1 Elevation - Door Pair
StileLite-200 Series Interior
SCALE : 3/8" = 1'-0"
144



1 Elevation - Corners
StileLite-200 Series Interior
SCALE : 3/8" = 1'-0"
144



1 Head
StileLite 200 Interior
SCALE : 6"=1'-0"
2



7 Inside Corner Mullion
StileLite 200 Interior
SCALE : 6"=1'-0"
2

2 Joint
StileLite 200 Interior
SCALE : 6"=1'-0"
2



8 Outside Corner Mullion
StileLite 200 Interior
SCALE : 6"=1'-0"
2



3 Head-Stacked
StileLite 200 Interior
SCALE : 6"=1'-0"
2



5 Door Jamb
StileLite 200 Interior
SCALE : 6"=1'-0"
2



4 Sill
StileLite 200 Interior
SCALE : 6"=1'-0"
2

TEST STANDARDS	
WALL SYSTEMS	DOORS
ASTM E-119	NFPA-252
NFPA-251	UL-10C
UL-263	
CANADIAN 4S-101	CANADIAN 4S-104

GLAZING	
	INTERIOR
USAGE	INTERIOR
THICKNESS	1" [25 MM] + - 2MM
WEIGHT/SQ.FT.	12.3 LBS [60 KG/SQ.M]
LIGHT TRANSMISSION	81%
SOUND REDUCTION	Rw=42 dB
SAFETY RATING	CPSC 16CFR1201 CAT.II 400 FT. LBS. ANSI Z97.1
FIRE RATING	60 MINUTES
R-VALUE	1.14
U-VALUE	0.881

Hardware Schedule

Family	Model	Manufacturer	URL	Type Comments
Closer	4041R	LCN	www.lcn-Ingersollrand.com	LCN CLOSER W/18PA PLATE
Continuous Hinge	CHSB3HD1	PEMKO	www.pemko.com	PEMKO CONTINUOUS HINGE
Cylinder	20-022 626	SCHLAGE	www.schlage.com	SCHLAGE CONVENTIONAL CYLINDER
Door Handle	9827L-F	VON DUPRIN	www.vonduprin.com	VON DUPRIN LEVER, KEY LOCKS AND UNLOCKS
Exit Device	9827L-F 630	VON DUPRIN	www.vonduprin.com	VON DUPRIN EXIT DEVICE

FINISH OPTIONS	DESCRIPTION
STANDARD PRIMER	PROPRIETARY EPA APPROVED ALKYD PRIMER: READY FOR PAINTING BY OTHERS
FINISH PAINTING	FACTORY FINISH PAINTED WITH TNEMEC 1075 ENDURA SHIELD II ACRYLIC POLYURETHANE [ALIPHATIC] AVAILABLE IN STANDARD OR CUSTOM COLORS
STAINLESS STEEL TEXTURED: NO. 4 FINISH	A LIGHTLY GRAINED SURFACE PRODUCED BY SINGLE DIRECTIONAL ABRAIDING.
STAINLESS STEEL TEXTURED: NO. 8 FINISH	MIRROR POLISHED, OBTAINED BY POLISHING WITH SUCCESSIVELY FINER ABRAISIVES, THEN BUFFED WITH VERY FINE COMPOUND
STAINLESS STEEL TEXTURED: ANGEL HAIR FINISH	PRODUCED BY MEDIUM-FINE GRIT ORBITAL SANDING: NON DIRECTIONAL
STAINLESS STEEL TEXTURED: NON-DIRECTIONAL FINISH	PRODUCED BY FINE GRIT ORBITAL SANDING [NON-DIRECTIONAL] ON NO. 2B [MILL FINISH] STAINLESS STEEL.
STAINLESS STEEL TEXTURED: RANDOM SWIRL FINISH	GRITTED SURFACE PRODUCED BY RANDOM MULTI-DIRECTIONAL ABRAIDING.
STAINLESS STEEL TEXTURED: BEAD BLASTED FINISH	PRODUCED BY BEAD-BLASTING NO. 2B [MILL] STAINLESS STEEL. SURFACE HAS MATTE FINISH WITH A DULL TO GLOSSY SHEEN DEPENDING ON SIZE OF BEAD.

InterEdge Technologies
Escondido, CA.

StileLite™ Frames
60-MINUTE TEMPERATURE-RISE FRAMING

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

No.	Description	Date

StileLite-200 Series Interior

Project Number	Project Number
Date	Issue Date
Drawn By	Author
Checked By	Checker

A101

Scale

10/9/2009 12:34:21 PM