

E1 Front Elevation - Single Door 2HR
3/8" = 1'-0"



E2 Front Elevation - Double Door 2HR
3/8" = 1'-0"



E3 Front Elevation 2HR
3/8" = 1'-0"



E4 Front Elevation - Corners 2HR
3/8" = 1'-0"



P1 Plan - Single Door 2HR
3/8" = 1'-0"



P2 Plan - Double Door 2HR
3/8" = 1'-0"



P3 Plan 2HR
3/8" = 1'-0"



P4 Plan - Corners 2HR
3/8" = 1'-0"



1 Head / Jamb
6" = 1'-0"



7 Inside Corner
6" = 1'-0"



2 Vertical Mullion
6" = 1'-0"



8 Outside Corner
6" = 1'-0"



3 Horizontal Mullion
6" = 1'-0"



11 Door Head
6" = 1'-0"

TEST STANDARDS	
WALL SYSTEMS	DOORS
ASTM E-119	NFPA-252
NFPA-251	UL-10C
UL-263	
CANADIAN 4S-101	CANADIAN 4S-104



4 Sill
6" = 1'-0"



12 Door Jamb
6" = 1'-0"



13 Door Jamb @ Hinge
6" = 1'-0"

Hardware Schedule

Count	Family	Model	Manufacturer	URL	Type Comments
6	Closer-LCN	4041R	LCN	www.lcn-ingersollrand.com	LCN CLOSER W/18PA PLATE
6	Continuous_Hinge-Pemko	CHS83HD1	PEMKO	www.pemko.com	PEMKO CONTINUOUS HINGE
6	Cylinder-Schlage	20-022 626	SCHLAGE	www.schlage.com	SCHLAGE CONVENTIONAL CYLINDER
6	Door_Handle-Von_Duprin	9827L-F	VON DUPRIN	www.vonduprin.com	VON DUPRIN LEVER, KEY LOCKS AND UNLOCKS
6	Exit_Device-Von_Duprin	9827L-F 630	VON DUPRIN	www.vonduprin.com	VON DUPRIN EXIT DEVICE

Mullion Schedule 2HR

Count	Type	Length	Keynote
4	Door_Jamb_Left-InterEdge-StileLite300-2HR-Interior-3 1/2"	15' - 7 1/4"	08 43 00.A2
7	Door_Jamb_Right&Head-InterEdge-StileLite300-2HR-Interior-3 1/2"	31' - 1 5/16"	08 43 00.A4
28	Head-InterEdge-StileLite300-2HR-Interior-3 1/2"	101' - 5 1/8"	08 43 00.A8
17	Horizontal-InterEdge-StileLite300-2HR-Interior-3 1/2"	57' - 3"	08 43 00.A8
5	Inside_Corner-InterEdge-StileLite300-2HR-Interior-3 1/2"	9' - 7 1/4"	08 43 00.B11
11	Jamb_Left-InterEdge-StileLite300-2HR-Interior-3 1/2"	28' - 9 3/4"	08 43 00.A5
5	Outside_Corner-InterEdge-StileLite300-2HR-Interior-3 1/2"	10' - 0"	08 43 00.B10
12	Sill-InterEdge-StileLite300-2HR-Interior-3 1/2"	43' - 0 1/8"	08 43 00.A10
24	Vertical-InterEdge-StileLite300-2HR-Interior-3 1/2"	45' - 5 1/8"	08 43 00.A9

Door Schedule

Count	Family and Type	Manufacturer	URL	Type Comments	Panel Type	Width	Height
1	Door-Double-Stiles-Fire_Rated: 5.5" for 1" glass	Stiles	www.stilesdoor.com	STILES FIRE RATED DOUBLE HM DOOR & FRAME	Door_Panel-Stiles_Fire_rated : 1 3/4"	6' - 0"	8' - 0"
1	Door-Double-Stiles-Fire_Rated: 7"	Stiles	www.stilesdoor.com	STILES FIRE RATED DOUBLE HM DOOR & FRAME	Door_Panel-Stiles_Fire_rated : 1 3/4"	6' - 0"	8' - 0"
1	Door-Single-Stiles-Fire_Rated: 5.5" for 1" glass	Stiles	www.stilesdoor.com	STILES FIRE RATED SINGLE HM DOOR & FRAME	Door_Panel-Stiles_Fire_rated : 1 3/4"	4' - 0"	8' - 0"
1	Door-Single-Stiles-Fire_Rated: 7"	Stiles	www.stilesdoor.com	STILES FIRE RATED SINGLE HM DOOR & FRAME	Door_Panel-Stiles_Fire_rated : 1 3/4"	4' - 0"	8' - 0"

4

Panel Schedule 2HR

Count	Family and Type	Width	Height	Area	Type Comments
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	1' - 10 23/32"	9' - 9 7/16"	18.53 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	2' - 9 7/16"	2' - 10 5/8"	16.08 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	2' - 9 7/16"	4' - 11 13/16"	27.78 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	2' - 10 5/8"	1' - 10 5/8"	10.88 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 1 15/32"	2' - 10 5/8"	9.01 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 1 15/32"	6' - 10 5/8"	21.50 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 7 19/32"	1' - 11 1/8"	7.00 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 7 19/32"	2' - 10 5/8"	10.48 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 7 19/32"	4' - 11 5/16"	17.95 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 9 3/16"	2' - 10 5/8"	10.87 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 9 3/16"	6' - 10 5/8"	25.93 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 9 7/16"	2' - 10 5/8"	21.85 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 9 7/16"	4' - 11 13/16"	37.75 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 10 5/8"	1' - 10 5/8"	14.65 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 10 5/8"	1' - 11 1/8"	7.49 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 10 5/8"	2' - 10 5/8"	22.42 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 10 5/8"	4' - 11 5/16"	19.20 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 10 5/8"	6' - 10 5/8"	26.75 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 11 13/16"	1' - 9 7/16"	7.12 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 11 13/16"	3' - 5 31/32"	27.86 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
2	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	3' - 11 13/16"	6' - 3 9/32"	50.00 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
1	Panel-Glazing-InterEdge-Pyrobel-Interior-Fire_Rated: 120 - 2 1/8" Interior	5' - 11 13/16"	1' - 9 7/16"	10.69 SF	2 1/8" PYROBEL-120 FIRE RATED INTERIOR GLAZING
31				421.79 SF	

InterEdge Technologies
Berkeley, CA

StileLite™ Frames
120-MINUTE TEMPERATURE-RISE FRAMING

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

Consultant
Address
Address
Address
Phone

No.	Description	Date

StileLite-300 Series 2HR - Interior

Project Number	Project Number
Date	Issue Date
Drawn By	Author
Checked By	Checker

A101

Scale: As indicated

3/25/2011 4:50:24 PM